

CONCRETE & DRIVEWAY

Professional Strength Concentrated Formula for Pressure Washers

Dissolves stubborn grease, oil and dirt stains on concrete, asphalt, brick and stone surfaces

Clean Shot Concrete & Driveway is a professional strength product for the toughest jobs, including the removal of soils caused by oil, grease, dirt, soot and grime as well as thoroughly cleans stains caused by mold, mildew and algae.



| 12.0-13.0 |
|------------|
| Liquid |
| Aromatic |
| Violet |
| 4/1 Gallon |
| |

DIRECTIONS FOR USE:

- 1. Before starting, thoroughly wet plants and shrubbery and saturate surrounding grass areas. Cover any exposed vegetation with waterproof
- 2. Holding nozzle 8 to 12 inches from surface at 45 degree angle, use low-pressure spray to apply, working from bottom to t top. Evenly apply one coat of product.
- Allow product to remain on surface for several minutes, but do not allow to dry on surface.
- Using high pressure, rinse the surface thoroughly.
- Thoroughly rinse all plants and shrubbery with water.

NOTE: Extremely soiled surfaces may require scrubbing with a bristle brush, and a second application may be needed. Mold and mildew stains and severe grease and oil stains may not be completely removed from porous surfaces. Repeat applications may lighten stains, but may not completely remove stains. For use in pressure wash machines with down stream chemical injectors, machines without this capability may require manual application, using this machine only to rinse with surface

RECOMMENDED DILUTIONS:

Light Cleaning: Dilute 5-6 ounces of this product per 1 gallon of water. Normal Cleaning: Dilute 7-9 ounces of this product per 1 gallon of water. Dilute 10-12 ounces of this product per 1 gallon of water. **Heavy Cleaning:**

IMPORTANT SAFETY INFORMATION:

WARNING: IRRITANT: KEEP OUT OF REACH OF CHILDREN. CAUSES EYE AND SKIN IRRITATION.

Avoid contact with skin, eyes, or clothing. Do not swallow. Do not mix with other chemicals. Wash hands after use. Read all warnings before use.

PRECAUTIONS: Never mix this or any product with another chemical. Always test on an inconspicuous area in advance of use. When using on painted surfaces, water pressure alone may remove paint. Exposure to the sun may cause discoloration and/or oxidation of exterior surfaces, including paint, vinyl, aluminum, wood, and other materials. Use of this product to clean such surfaces will remove dirt and other contaminates which may highlight this discoloration. Store in areas inaccessible to small children. Do not reuse empty container. Wrap and discard in trash. Any disposal practice must be in compliance with local, state and federal regulations.

EYE CONTACT: Flush with cool water for several minutes.

SKIN CONTACT: Wash with soap and water.

INHALATION: Remove person to fresh air. If symptoms persist or are severe, obtain medical attention. IF SWALLOWED: Do not induce vomiting. Call a physician or Poison Control Center immediately.

CONTAINS: 2-butoxyethanol (CAS# 111-76-2), disodium metasilicate (CAS# 6834-92-0)

Emergency Response Number: 1-800-255-3924





SOLUTIONS FOR A CLEANER WORLD®