FINISH

LUMINATE

Low Maintenance Floor Finish

- · Natural shine, low maintenance, and long-lasting durability
- · Multi-polymer formula, reduced scratching, and superior hardness
- · Ease of removability for least amount of labor

The exceptional multi-polymer finish brings out the natural shine, resists scratching, and prolongs the time between stripping. Crystal clear, low maintenance floor finish. May be used on all resilient flooring and most sealed stone. Extremely hard, durable finish protects your floor and makes for easy clean-up and removability. Tough protection and easy maintenance ensure value and make a nice reflection on you. The exceptional choice for education and health care facilities where little to no time is available for constant floor burnishing. Recommended for low to medium maintenance procedures.

DIRECTIONS FOR USE:

INITIAL APPLICATION: Completely strip all old wax or finish. Be careful to follow the "Directions for Use" for the selected stripper. Remove the stripping solution with wet vac or auto-scrubber. Detail mop to remove all residue and allow the floor to completely dry. Repeat if necessary. The floor must be clean, dry, and free of all residue. Apply 1 or 2 even coats (optional, based on the condition of the floor), and let dry. Apply finish in uniform, thin coats. Allow each coat to dry for 20 - 30 minutes, or until the surface is completely dry to the touch, before applying additional coats. Allow an extra 10 minutes of drying time for each additional coat. A total of 4-6 coats of finish are recommended.

ROUTINE MAINTENANCE: Sweep large debris and remove. Dust mop to remove dry soil, then damp mop or automatic scrub with a neutral floor cleaner. Buff or burnish the floor as desired. The use of a restorer is recommended to extend the time between top scrub and re-coating.

INTERIM MAINTENANCE: Sweep large debris and remove. Dust mop to remove dry soil, then damp mop or automatic scrub with neutral floor cleaner. Top scrub with a restorer and recommended floor pad to remove top soiled layers of finish. The floor must be clean, dry, and free of all residue. Apply 1-2 coats of finish as directed under "Initial Application".

IMPORTANT SAFETY INFORMATION:

KEEP FROM FREEZING

Slip resistance meets or exceeds ASTM D 2047-04 James Machine 0.5 minimum.

PRECAUTIONS:

If medical advice is needed, have the product container or label at hand. Keep out of reach of children. Read the label before use. Store in cool, dry conditions in well-sealed receptacles. Dispose of contents and container in accordance with local, regional, national, and international regulations.

FIRST AID:

IF ON SKIN: Generally the product does not irritate the skin. Rinse with warm water. If skin irritation continues, consult a doctor.

IF IN EYES: Remove contact lenses if worn. Rinse opened eye for several minutes under running water. Then consult a doctor.

IF INHALED: Supply fresh air; consult doctor in case of complaints.

IF SWALLOWED: Do not induce vomiting; call for medical help immediately. Rinse out mouth and then drink plenty of water.

CONTAINS:

Diethylene glycol monoethyl ether (111-90-0), Ammonia, aqueous solution (1336-21-6).



APPLICATIONS

- Nursing homes
- Schools
- Hospitals
- Health care applications

SPECIFICATIONS

Color	White
Fragrance	Acrylic
pH Range	8.0 - 9.0
Form	Liquid
Dilution Range	Ready to Use

PACKAGING	
4/1 Gallon	100696-505858
5 Gallon Pail	100696-505859
55 Gallon Drum	100696-505860

PROP 65 INFO

WARNING: This product can expose you to chemicals including1,4-dioxane which is known to the State of California to cause Cancer. For more information go to www.P65Warnings.ca.gov.



Contact your Account Representative for more information 7373 Rowlett Park Dr., Tampa, FL 33610 | 813.237.6463 | Emergency #800.255.3924 | theochem.com ©2022 Theochem Laboratories Inc. All right reserved. | Made in the USA