

FLOOR CARE FINISH

TITANIUM

Professional Floor Finish

- Urethane fortified ultra-high-speed finish
- Resists black heel marks, excellent durability
- Superior gloss level

This modern floor coating, fortified with urethane and acrylic polymers, produces a protective barrier that resists black marks, scuffs, scratches, and abrasions. Its uncommon durability delivers a classic “wet look” shine that reduces labor by lasting longer between maintenance cycles. This product is ideal for resilient flooring and may be used on concrete or terrazzo. Maintenance procedures may include spray buffing, high and ultra-high-speed burnishing. Outstanding for maintaining difficult “hot spot” floor areas.

DIRECTIONS FOR USE:

Remove all old sealers, waxes, and finishes. Thoroughly rinse so that no stripper or alkaline residue remains on the floor. Allow the floor to dry thoroughly before applying. Apply thin coats with a rayon mop allowing the finish to dry completely between coats. For best results, only apply four coats in 24 hours.

NOTE: Maintain floor by keeping it dust and dirt free. To remove heel marks (or scuffing) apply a restorer. After drying, burnish with high-speed equipment. This finish also responds to spray buffing with conventional speed floor machines using beige or red spray buff pads. Re-coat when restoration no longer returns floor to “wet-look”. Before re-coating, scrub the floor with an auto-scrubber using a neutral cleaner.

IMPORTANT SAFETY INFORMATION:



DANGER

May damage fertility or the unborn child. Route of exposure: Oral.

PRECAUTIONS:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection. Store locked up. Dispose of contents and container in accordance with local, regional, national and international regulations.

FIRST AID:

If exposed or concerned, get medical attention.

CONTAINS:

Carbitol (CAS# 111-90-0) and N-methyl-2-pyrrolidone (CAS# 872-50-4)



APPLICATIONS

- Nursing homes
- Schools
- Hospitals
- Health care applications

SPECIFICATIONS

Color	White
Fragrance	Acrylic
pH Range	7.0 - 9.0
Form	Liquid
Dilution Range	Ready to Use

PACKAGING

4/1 Gallon	103665-507307
5 Gallon Pail	103665-507306

PROP 65 INFO

! **WARNING:** This product can expose you to chemicals including N-methyl-2-pyrrolidone which is known to the State of California to cause birth defects or other reproductive harm. Exposure during pregnancy may affect development of the child, and may also harm the male and female reproductive systems. For more information go to www.P65Warnings.ca.gov.



Contact your Account Representative for more information

7373 Rowlett Park Dr., Tampa, FL 33610 | 813.237.6463 | Emergency #800.255.3924 | theochem.com

©2022 Theochem Laboratories Inc. All right reserved. | Made in the USA